

Waterborne Clear Wood Finish

Get the performance of lacquer in a water-based acrylic formula.

Waterborne Clear Wood Finish is crosslinking acrylic technology, formulated to embody the positive qualities of our Clear Wood Finish brushing lacquer, without the environmental and flammability issues of the original solvent formulation. Ideal for the professional and DIYer alike. It is very easy to apply, and offers the best performance of any waterborne finish on the market. Enriches finished or unfinished wood while delivering superior durability along with a strong mar resistant finish.

Quick & Easy.

- Apply with a brush, pad, roller, or spray application.
- Self-leveling formula for easy application.
- Crystal clear finish.
- Dries to the touch in 30 minutes. Recoat in 2 hours.
- Resists common household chemicals.

Environmentally Friendly.

- Low odor.
- Cleans up with soap and water.
- Meets all VOC requirements.

Seals and Finishes Indoor Areas.

Waterborne Clear Wood Finish seals, finishes, and gives a rich luster to many interior wood surfaces (except floors). Ideal for :

- Furniture.
- Doors and woodwork.
- Cabinets and paneling.
- Antiques.
- Top coat over faux finishes.
- Fine for use on rose woods and other exotic hardwoods.
- Excellent for use on crafts and toys.

Finishes and Sizes.

- Available in three finishes: Gloss, Semi-Gloss, and Satin.
- Sizes include: Aerosol, Quart, Gallon, and 5-Gallon Pail.



APPLICATION:

1. Sand the wood to proper smoothness (do not use steel wool) and remove dust. Apply stain if desired.
2. If using stain, follow the instructions on the can to insure proper application and dry times.
3. Apply Waterborne Clear Wood Finish with a brush, pad, roller, or spray.
4. Let dry 2 hours between coats. Apply at least 3 coats.
5. Sand between coats using fine (220 grit) sandpaper and remove sanding dust.
6. Clean brushes and/or other application tools with soap and water.